

JMDTOOLS®
 —金美达工具—
 NANJING JINMEIDA TOOLS CO.,LTD.





RECIPROCATING SAW BLADES

JMDTOOLS®
 —金美达工具—
 NANJING JINMEIDA TOOLS CO.,LTD.


地 址：南京市江宁滨江开发区天成路42号
 电 话：86-25-84950239 / 84950276 / 52428376
 传 真：86-25-52404499
 联系人：嵇媛媛/吕凤/杨向京
 邮 箱：jyy@njjmd.com lf@njjmd.com
 网 址：http://www.njjmd.com
 邮 编：211162

Add: No.42 Tian Cheng Road, Binjiang Economic
 Development Zone Jiangning District, Nanjing
 Tel: 86-25-84950239 / 84950276 / 52428376
 Fax: 86-25-52404499
 Contact: Yolanda Ji, Lv Feng, Yang Xiangjing
 E-mail: jyy@njjmd.com lf@njjmd.com
 Web: http://www.njjmd.com
 P C: 211162





Blue For metal



White For wood with metal



Grey For wood



Black For special applications

1/2" shank for reciprocating saws

For Atlas Copco, Black&Decker, Bosch, Flex, Hitachi, Makita, Metabo, Milwaukee, Porter Cable, Skil, Rockwell.

Flexible for metal

型号
Item

锯条总长
Total Length
(mm)

齿数
Teeth Per Inch

材料
Material



milled & wavy set

R123XF

150×19×0.9

8-14 Pro.

Bi-Metal

Thin to thick sheet metal (1-8mm),Thin to thick profiles (dia.5-100mm)

Flexible for metal



milled & wavy set


R422AF

100×19×0.9

24

Bi-Metal

Thin sheet metal (0.7-3mm) effortless, fine cut



milled & wavy set

R622AF

150×19×0.9

24

Bi-Metal

Thin sheet metal (0.7-3mm) fine pipes/profiles (dia.5-100mm)*effortless, fine cut



milled & wavy set

R922AF

225×19×0.9

24

Bi-Metal

Thin sheet metal (0.7-3mm) fine pipes/profiles (dia.5-175mm)*effortless, fine cut, flexible flush cut



milled & wavy set

R422EF

100×19×0.9

18

Bi-Metal

Thin sheet metal (1.5-4mm)



milled & wavy set

R622EF

150×19×0.9

18

Bi-Metal

Thin sheet metal (1.5-4mm) pipes/profiles (dia.5-100mm)



milled & wavy set

R922EF

225×19×0.9

18

Bi-Metal

Thin sheet metal (1.5-4mm) pipes/profiles (dia.5-175mm)*flexible flush cut



milled & wavy set

RBL422F

100×19×0.9

14+18

Bi-Metal

Clean for heavy metal 2x2 tooth geometry (14+18 TPI) ideal for clean cutting in thick metals and provides longer blade life



milled & wavy set

RBL622F

150×19×0.9

14+18

Bi-Metal

Clean for heavy metal 2x2 tooth geometry (14+18 TPI) ideal for clean cutting in thick metals and provides longer blade life



milled & wavy set

RBL922F


225×19×0.9

14+18


Bi-Metal

Clean for heavy metal 2x2 tooth geometry (14+18 TPI) ideal for clean cutting in thick metals and provides longer blade life

Progressive for metal

	型号 Item	锯条总长 Total Length (mm)	齿数 Teeth Per Inch	材料 Material
	RS422BF	100×16×0.9	14	Bi-Metal
milled & wavy set		Medium-thick sheet metal (1.5-6mm) especially for curved cuts		
	R422BF	100×19×0.9	14	Bi-Metal
milled & wavy set		Thick sheet metal (3-8mm) fast cut		
	R622BF	150×19×0.9	14	Bi-Metal
milled & wavy set		Thick sheet metal (3-8mm) Solid pipes/profiles (dia.10-100mm) fast cut		
	R922BF	225×19×0.9	14	Bi-Metal
milled & wavy set		Thick sheet metal (3-8mm) Solid pipes/profiles (dia.10-100mm) fast cut		
	RBM422F	100×19×0.9	8+10	Bi-Metal
milled & side set		Speed for heavy metal Patented 2x2 tooth pitch (8+10TPI) ideal for fast cuts in metal		
	RBM622F	150×19×0.9	8+10	Bi-Metal
milled & side set		Speed for heavy metal Patented 2x2 tooth pitch (8+10TPI) ideal for fast cuts in metal		
	RBM922F	225×19×0.9	8+10	Bi-Metal
milled & side set		Speed for heavy metal Patented 2x2 tooth pitch (8+10TPI) ideal for fast cuts in metal		

Heavy for metal

	R825BF	200×19×1.25	14	Bi-Metal
milled & wavy set		Medium-thick to thick sheet metal (2-8mm) Solid pipes/profiles (dia.10-150mm)		
	R825HF	200×19×1.25	10	Bi-Metal
milled & side set		Thick sheet metal (3-12mm), solid pipes/profiles (dia.10-150mm) fast cut		
	R825VF	200×19×1.25	10-14 Pro.	Bi-Metal
milled & wavy set		Medium-thick to thick sheet metal (2-12mm)Solid pipes/profiles (dia.10-150mm) effortless, fine cut		

1/2" shank for reciprocating saws

For Atlas Copco, Black&Decker, Bosch, Flex, Hitachi, Makita, Metabo, Milwaukee, Porter Cable, Skil, Rockwell.

Heavy for metal

	型号 Item	锯条总长 Total Length (mm)	齿数 Teeth Per Inch	材料 Material
	R620CF	150×22×1.6	9	Bi-Metal
milled & side set		Steel plate (4-10mm), solid pipes/profiles (dia.20-100mm) ideal for pipe cutting device for rescue/demolition work powerful, coarse cut		
	R920CF	225×22×1.6	9	Bi-Metal
milled & side set		Steel plate (4-10mm), solid pipes/profiles (dia.20-175mm) ideal for pipe cutting device for rescue/demolition work powerful, coarse cut		
	RB620F	150×22×1.6	8+10	Bi-Metal
milled & side set		Demolition for metal 2x2 tooth pitch (8+12TPI) ideal for fast cutting in metals		
	RB920F	225×22×1.6	8+10	Bi-Metal
milled & side set		Demolition for metal 2x2 tooth pitch (8+12TPI) ideal for fast cutting in metals		

Flexible for wood with metal

	R622HF	150×19×0.9	10	Bi-Metal
milled & side set		wood with nails/metal (5-100mm), sheet metal, pipes, aluminium profiles (3-12mm), pallets		
	R922HF	225×19×0.9	10	Bi-Metal
milled & side set		For pallet repair, wood with nails/metal (5-175mm), sheet metal, pipes, aluminium profiles (3-12mm) flexible flush cut		
	R622VF	150×19×0.9	10-14 Pro.	Bi-Metal
milled & wavy set		wood with nails/metal (5-100mm), sheet metal, pipes, aluminium profiles (3-10mm), pallets profiles (dia.3-100mm)		
	R922VF	225×19×0.9	10-14 Pro.	Bi-Metal
milled & wavy set		wood with nails/metal (5-100mm), sheet metal, pipes, aluminium profiles (3-10mm), pallets profiles (dia.3-100mm)		
	R1222VF	300×19×0.9	10-14 Pro.	Bi-Metal
milled & wavy set		wood with nails/metal (5-250mm), sheet metal, aluminium profiles (3-10mm), plastic profiles (dia.3-250mm) flexible flush cut		

Progressive for wood with metal



milled & side set

型号 Item	锯条总长 Total Length (mm)	齿数 Teeth Per Inch	材料 Material
------------	------------------------------	----------------------	----------------

R345XF	200×19×1.25	6-12 Pro.	Bi-Metal
--------	-------------	-----------	----------

wood with nails/metal (5-250mm), sheet metal, aluminium profiles (3-10mm), plastic profiles (dia.3-250mm) flexible flush cut

Heavy for wood with metal



milled & side set

R611DF	150×19×1.25	6	Bi-Metal
--------	-------------	---	----------

wood with nails/metal, chipboards (10-100mm), plastic profiles (dia.5-100mm), plastics/glass fibre reinforced plastics, solid (8-50mm), window frames: wood+metal especially for plunge cut



milled & side set

RS611DF	150×16×1.25	6	Bi-Metal
---------	-------------	---	----------

wood with nails/metal, chipboards (10-100mm), plastics/glass fibre reinforced plastics, solid (8-50mm) especially for curve cut



milled & side set

R922DF	225×19×1.25	6	Bi-Metal
--------	-------------	---	----------

wood with nails/metal, chipboards (10-175mm), plastic profiles (dia.5-175mm), plastics/glass fibre reinforced plastics, solid (8-50mm)



milled & side set

R1211DF	300×19×1.25	6	Bi-Metal
---------	-------------	---	----------

wood with nails/metal, chipboards (10-250mm), aerated concrete (10-250mm), plastics/glass fibre reinforced plastics, profiles (5-60mm)



milled & side set

R610DF	150×22×1.6	6	Bi-Metal
--------	------------	---	----------

wood with nails/metal, chipboards (10-100mm), plastics/glass fibre reinforced plastics, solid (8-50mm), wall cutouts: wood+metal (<75mm) *for rescue/demolition work



milled & side set

R910DF	225×22×1.6	6	Bi-Metal
--------	------------	---	----------

wood with nails/metal, chipboards (10-175mm), plastics/glass fibre reinforced plastics, solid (8-50mm), wall cutouts: wood+metal (<150mm) *for rescue/demolition work



milled & side set

RB611F	150×22×1.6	5-8 Pro.	Bi-Metal
--------	------------	----------	----------

Demolition for wood nails Variable 5/8 tooth pitch ideal for heavy demolition work in wood with nails, but strong enough to handle thick metals and other materials

1/2" shank for reciprocating saws

For Atlas Copco, Black&Decker, Bosch, Flex, Hitachi, Makita, Metabo, Milwaukee, Porter Cable, Skil, Rockwell.

Heavy for wood with metal



milled & side set

型号 Item	锯条总长 Total Length (mm)	齿数 Teeth Per Inch	材料 Material
------------	------------------------------	----------------------	----------------

RB922F	225×22×1.6	5-8	Bi-Metal
--------	------------	-----	----------

Demolition for wood nails Variable 5/8 tooth pitch ideal for heavy demolition work in wood with nails, but strong enough to handle thick metals and other materials



milled & side set

RB1222F	300×22×1.6	5-8	Bi-Metal
---------	------------	-----	----------

Demolition for wood nails Variable 5/8 tooth pitch ideal for heavy demolition work in wood with nails, but strong enough to handle thick metals and other materials

Basic for wood



milled & side set

R617K	150×19×1.25	3	HCS
-------	-------------	---	-----

coarse wood, free of nails (20-100mm), pruning green wood (dia.<100mm)
*especially for curved cuts



milled & side set

R922K	225×19×1.25	3	HCS
-------	-------------	---	-----

coarse wood, free of nails (20-175mm), fuel wood (dia.20-175mm)



milled & side set

R1217K	300×19×1.25	3	HCS
--------	-------------	---	-----

coarse wood, free of nails (20-250mm), pruning green wood (dia.<250mm)

Progressive for wood



ground & side set

R234X	200×19×1.25	6-10 Pro.	HCS
-------	-------------	-----------	-----

construction timber (6-150mm), boards: chip, MDF (medium-density fibreboard) (6-60mm), plywood, plastic (6-150mm), wooden panels(<175mm)

Top for wood



ground & side set

R644D	150×19×1.25	6	HCS
-------	-------------	---	-----

construction timber (6-100mm), wooden panels(<75mm), boards: chip, MDF (6-60mm), plywood, plastic (6-100mm) especially for plunge cuts



ground & side set

R1021L	240×19×1.5	5	HCS
--------	------------	---	-----

coarse wood, free of nails (15-190mm), pruning green wood (dia.<190mm), fuel wood (dia.15-190mm)

Top for wood

型号
Item

锯条总长
Total Length
(mm)

齿数
Teeth Per Inch

材料
Material



ground & side set

R1031K	240×19×1.5	3	HCS
--------	------------	---	-----

fuel wood, damp wood (dia.15-190mm)

Special for plaster



milled & side set

R628DF	150×19×1.25	6	Bi-Metal
--------	-------------	---	----------

plasterboard (8-100mm) especially for plunge cuts, tear-free cut

Special for cast with brick



coated

R930RFI	225×19×1.25	30grit	TC
---------	-------------	--------	----

cast-steel pipes (max.dia.6"), red brick (10-175mm), glass fibre reinforced plastics/epoxy (3-175mm)

Special for soft-material



edge

R613A	150×19×1.0	knife edge	HCS
-------	------------	------------	-----

polystyrene, insulation (10-100mm)


RECIPROCATING SAW BLADES SETS



1PC Card Packing



2PC Single Blister



2PC Cardboard



2PC PVC Bag



4PC Single Blister



5PC Double Blister



5PC Plastic Case



5PC PVC Bag



5PC PVC Bag



5PC Double Blister



10PC Single Blister



10PC Plastic Case



28PC Double Blister